

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-087430

(43)Date of publication of application : 03.04.2001

(51)Int.Cl.

A63B 53/04

(21)Application number : 11-266693

(71)Applicant : HONMA GOLF CO LTD

(22)Date of filing : 21.09.1999


(72)Inventor : HONMA HIROAKI

## (54) HEAD FOR GOLF CLUB

## (57)Abstract:

PROBLEM TO BE SOLVED: To provide a head 1 for golf clubs which is provided with a cavity 5 of a recessed part form on the back of the head 1 having a face and with which the face may be reinforced, the deformation of the clubface when hitting a ball may be thereby prevented and a good ball hitting feel may be assured.

SOLUTION: The cavity 5 of the head 1 for golf clubs which is provided with the cavity 5 of the recessed part form on the back of the head 1 a face is provided with a rib 6 for making the bending in the central part of the face when hitting the ball difficult.



## LEGAL STATUS

[Date of request for examination] 29.03.2000

[Date of sending the examiner's decision of rejection] 30.10.2002

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's  
decision of rejection]

[Date of requesting appeal against examiner's  
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office

=


\* NOTICES \*

Japan Patent Office is not responsible for any damages caused by the use of this translation.


1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

DRAWINGS



[Drawing 1]




[Drawing 2]




[Drawing 3]




[Drawing 4]



[Drawing 5]




[Drawing 7]



[Drawing 6]


(A)




(B)

テストピース	フェース肉厚	リブ補強	重量削減効果	変形荷重	打球感
A	4.0 mm	なし	(基準値)	1700kgf	○
B	3.5 mm	なし	-7.5 g	1300kgf	○
C	3.0 mm	なし	-15.0 g	900kgf	△
D	2.5 mm	なし	-22.5 g	500kgf	×
E	2.5 mm	あり	-16.5 g	1400kgf	○


[Drawing 8]




[Drawing 9]




[Drawing 10]




[Drawing 11]




[Drawing 12]




[Drawing 13]




[Drawing 14]




[Drawing 15]



[Drawing 16]



[Drawing 17]



---

[Translation done.]